

Serial No.: 09/771,313

IN THE UNITED STATES
PATENT AND TRADEMARK OFFICE

Applicants: Thomas Clyde Banwell
Nim Kwna Cheung
Phiroz Madon

Case: APP 1237

Serial No.: 09/771,313

Filed: January 28, 2001

Group Art Unit: Not Yet Assigned

Examiner: Not Yet Assigned

Title of Invention: **PHYSICAL LAYER AUTO-DISCOVERY FOR MANAGEMENT OF
NETWORK ELEMENTS**

**THE COMMISSIONER OF PATENTS
WASHINGTON, D.C. 20231**

PRELIMINARY AMENDMENT

SIR:

Prior to the Examination of the above-identified application, please amend
the above-identified application as follows:

IN THE SPECIFICATION

Please substitute for the specification of record, the attached clean form of the
specification.



Serial No.: 09/771,313

REMARKS

In accordance with 37 CFR 125(b), applicants respectfully submit the substitute specification attached hereto. The original specification is being amended to correct several typographical errors. Applicants respectfully believe that the substitute specification does not contain any new matter. Further, in accordance with 37 CFR 125(b), applicants are attaching herewith a marked up copy of the specification of record wherein all the changes are highlighted.

Applicants respectfully submit that the submittal of this substitute specification does not require payment of any additional fees since the claims remain unchanged. Nonetheless, if any additional fees are required, please charge Deposit Account Number 02-1820 with such fee(s).


Favorable consideration and issuance of this application is therefore respectfully requested.

Respectfully submitted,

By:

Orville Cockings
Attorney for Applicants
Reg. No. 42,424
973-829-2370


Date: May 29, 2001



Serial No.: 09/771,313

**MARKED UP VERSION OF ORIGINAL SPECIFICATION SHOWING ALL
CHANGES MADE**

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207



PHYSICAL LAYER AUTO-DISCOVERY FOR MANAGEMENT OF NETWORK ELEMENTS

RELATED APPLICATIONS

5 The present application claims the benefit of U.S. Provisional Application Number 60/179,002 filed on January 28, 2000 and entitled "Method and System to Support Interoperable Network Elements in an Optical Network".

FIELD OF THE INVENTION

10 This invention generally relates to the operation and management of telecommunications network and more specifically to the operation and management of network elements within the public switched telephone network.

BACKGROUND

15 A network may be considered to be a collection of network elements that communicate with each other over physical links or paths. The network elements can be routers, switches, multiplexer/demultiplexers, etc. The physical links or paths can comprise copper cable, coaxial cable, or fiber cable. In addition to the network elements and links, the network also comprises a group of network management systems that perform the task of operating, administering, managing, and provisioning the network elements. From the view of the network management
20 system the links or paths and network elements form a network topology which includes a hierarchical structure. As such, when new services are requested network management systems are used to modify the settings in the appropriate network elements, establish new links, and update the network topology.

In order to adequately manage a network, a network management system (NMS), such as a provisioning system, needs to have an accurate view of the network topology in a database. The network topology database typically contains objects representing specific network elements (NEs), links, and their connectivity.

5 When the configuration of the real network changes, the network topology database must be changed in order to accurately track it.

Currently, the method for updating the network topology database is largely manual, particularly in the case of optical networking physical layer equipment (e.g., Wavelength Division Multiplex (WDM), Synchronous Optical NETwork (SONET), network elements) and links. For example, if a new SONET network element is installed or attached to the network, associated network topology equipment has to be manually entered into the associated network management system. If there is a fiber link change, this too needs to be manually updated into the network management system; and so on. Because the process is manual, the update system is labor-intensive, and prone to error. It is common to have the network management system view of the network topology either lagging behind the real network, or running ahead of it, or being just incorrect. Further, the traditional process of introducing a new network element to a network or establishing a new path may take weeks, even months. In addition, entering physical link information

10

15

20

into the topology database presents several other problems affecting accuracy.

Network element auto-discovery is currently available for network elements having Internet Protocol (IP) layer functionality. Specifically, as part of its protocol IP provides auto-discovery functionality which allows an IP router, for example, to gather the IP address of each IP layer equipment that is attached to that router.

25 More specifically, the Internet protocol suite provides highly structured tools that can

be used to support network auto-discovery, most notably: the IP address, which uniquely identifies hosts, routers, ports, and networks; utilities such as ping; and Signaling Network Management Protocol (SNMP). IP auto-discovery functionality therefore allows a network management system operating in the IP domain to
5 construct the topology of the IP network by simply communicating with the network elements in the network.

Equivalent auto-discovery functionality is not available for optical equipment operating at the physical layer. Thus, an network management system cannot automatically discover which physical link connects two network elements and which
10 ports are involved in the connection. Furthermore, there are multiple interrelated circuits at multiple protocol domains or layers: Wavelength Division Multiplex (WDM), Synchronous Optical NETwork (SONET), Asynchronous Transfer Mode (ATM), Internet Protocol (IP) to name a few. Moreover, each protocol domain (i.e., each
15 layer of the protocol stack) is typically managed by a separate network management system within a different network management sector. Finally, network management systems do not talk to each other.

To further illustrate the prior art limitations discussed above we refer to an illustrative network 100 as is shown in FIG. 1. FIG.1 depicts a SONET network 110 that is used as higher rate transport path between IP routers 112 and 113. The IP
20 routers in essence use the SONET network 110 to establish IP link 117. The figure also illustrates each domain being managed by different network management systems. Specifically, IP-Layer network management system 130 is only able to see the IP routers 112 and 113 in the network. In contrast, optical layer network management system 140 is only able to see the optical layer network elements 119.
25 The optical layer network elements 119 are invisible to the IP layer network

management system and the IP routers are invisible to the optical layer network management system 140. Thus, the result of an auto-discovery probe from network management system 130 would show only IP router 112 connected to IP router 113. In short, the entire SONET network 110 appears to the IP-Layer network management system as a single abstract IP link 117. Clearly, to be able to manage a multiple-protocol domain network, the network management system 130 should be able to find all the network elements by using auto-discovery.

Of utility then is a method and system that allows network management functionality across multiple network protocol domains.

SUMMARY

Our invention is a method and system for automatically discovering optical layer network elements.

In accordance with an aspect of our invention network elements comprising a network are each assigned a unique electronic serial number. In addition each port on a network element is uniquely defined. The unique port identifier and electronic serial number are then used by a point-to-point physical protocol to discover neighboring network elements. Each time a network element is connected to another network element via a physical link, each network element is able to determine the electronic model number, serial number and port identifier for the network element (NE) at the far end of the link. The network element subsequently sends this information to the network management system (NMS). The network management system is then able to use the information contained in the messages to construct a topology of the network.

Because our invention advantageously operates at the lowest layer all the network elements comprising a network are automatically discovered. Specifically,

in accordance with an aspect of our invention optical layer network elements as well as higher-layer network elements are automatically discovered. As such, a network management system implemented in accordance with our invention can acquire a more complete view of the entire network topology.

5 In accordance with another aspect of our invention network operators not desiring a complete view of the network topology may appropriately filter the discovered network topology.

10 Our invention operates autonomously and may be initiated by the network management system or the network elements within a network. The autonomous nature of our invention overcomes the prior art shortcomings by allowing for almost instantaneous updates of a network topology in response to the addition of a new network element or the addition or turning up a new link.

BRIEF DESCRIPTION OF THE DRAWINGS

15 FIG. 1 depicts prior art network management systems and subject network elements;

FIG. 2 is a high level illustration of our invention;

FIG. 3 illustratively depicts our method for uniquely identifying a network element in accordance with an aspect of our invention;;

20 FIG. 4A depicts the format of a request packet used accordance with an aspect of our invention;

FIG. 4B depicts the format of a response packet used in accordance with an aspect of our invention;

FIG. 5A depicts the method steps of an network management system initiated update in accordance with an aspect of our invention; and

FIG. 6 illustrates an exemplary network operating in accordance with our invention.

DETAILED DESCRIPTION

Turning to FIG. 2 there is depicted a high level view of an exemplary network in accordance with our invention. In FIG. 2 a first network element (NE) 210 is communicating with a second network element 220 over a link 225. Link 225 is preferably an optical link. As will become clearer below, the first and second network elements may be in different domains; for example, network element 210 may be an IP router or host whereas network element 220 may be a SONET Add Drop Multiplexer. Both network elements 210 and 220 are connected via links 228 and 229 to a network management system 230. The connections 228 and 229 is done using an Operating System/Network Element (OS/NE) protocol such as SNMP for IP domain network elements and connection 228 TL-1 for SONET equipment. In addition, the network management system 230 is connected either directly or indirectly to each network element 210 and 220 via a data network 233. Although we show each network element connected to in FIG. 2 those skilled in art will recognize that a network management system is usually able to indirectly communicate with several other network elements through the network element, so called gateway, that the network management system is directly connected to.

Each network element is seen exchanging, in accordance with our nomenclature, a hand-shake protocol 240. By use of the hand-shake protocol 240, along with the other aspects of our invention described below in more detail, our invention allows all the network elements comprising a network to be automatically discovered which in turn allows the network management system 230 to develop a complete view of the topology of the network across many network domains.

In addition to the hand-shake protocol 240 mentioned above, other aspects of our invention include a method for uniquely identifying a network element and an optical port on the network element and a method wherein each network element, either responsive to a request from a network management station or a self instantiated command/request, provides its identification, the identification of each optical port on the subject network element, and for each port connected to a link, the identification of the port at the far end of the fiber (the far end network element identification and the far end port identification).

In addition, each network element in FIG. 2 has functionality for encoding of an electronic model and serial number in accordance with an aspect of our invention as is illustrated by functional block 251. Block 251 is connected to a processor 252. Processor 252 is used in executing handshake protocol 240. Processor 252 also has as another input functional block 255. Block 255 is a physical layer auto-discovery functional module that can be initiated by network management system 230 or the network element in which it resides.

Turning to FIG. 3 there is illustrated our method for uniquely identifying a network element in a vendor or supplier neutral manner. At block 310 a network element is assigned two values: a network element model number and a network element serial number. These values are intended to uniquely identify each network element in much the same way that each cellular phone is uniquely identified. As such, we refer to these values as a network element's electronic serial number.

At block 320 the assigned model number and serial number are electronically encoded on the network element. The model number and serial may be advantageously represented by a character string in the network element. This step requires each network element to possess the intelligence to realize or know of its

own electronic serial number. Although currently each network element in the Public Switched Telephone Network (PSTN) is assigned a Common Language Equipment Identification (CLEI) codes and a Common Language Location Identification (CLLI) codes, those codes or values are not presently electronically encoded in the associated network element. More importantly, the current manual process of updating the network topology database is the precisely the process of associating the proper CLEI and CLLI code with proper links in the network.

Nonetheless, already existing values or codes, such as CLEI or CLLI code, can be used as an electronic serial number as long as the equipment possess the intelligence to know or recognize its own serial number and the serial number of other equipment. In short, the prior art is devoid of network elements that have the functionality that allows encoding of an electronic serial number for the purpose of our inventive concept. This functionality is illustrated in FIG. 2 as a software module 251 that runs on a processor 252.

In addition to each network element having an electronic serial number each port on a network element, in accordance with another aspect of our invention, is assigned a unique port identifier, block 321. Normally, every network element has its own manufacturer's syntax for identifying each port on the network element. In addition, each port on the network element is uniquely identified within this syntax. As such, the manufacturer's unique identifier may be used in accordance with our invention.

At block 330 each network element is represented in the network management system 230 (of FIG. 2) with an object that has the two values that comprise the electronic serial number. The network management system requires knowledge of the electronic serial number so that it (the network management

system) it is able to uniquely identify each network element within a network. The object representing the network element in the network management system can be loaded with the electronic serial number either automatically or manually. Automatic loading is more advantageous than manual loading since it removes the human error element from the process. Automatic loading would take place the first time the network element is installed in the network and connected to the network management system by having the network element autonomously inform the network management system of its presence. Manual loading of the network management system is not as advantageous as automatic loading, nevertheless manually loading the network element serial number in accordance with our invention represents a significant advance over the current practice. This is the case because only the electronic serial number of the network element needs to be loaded. In accordance with our invention each network element automatically discovers all the other network elements it is connected to and provides this information to an network management system, more precisely in the network topology database.

With each network element having an electronic serial number and each port on the network element being uniquely identified neighboring network elements then automatically communicate their respective connectivity information to each other as is shown at block 340 of FIG. 3. This communication is effected by way of a physical or optical layer auto-discovery function residing in each network element (represented as block 255 of FIG. 2). As previously discussed, while IP layer auto-discovery presently exists at the IP layer for equipment in the IP domain, ~~domain~~, IP layer auto-discovery is ~~however~~ is, however, vendor specific and done at the IP layer. Therefore, equipment operating at lower layers in the OSI stack are invisible using

vendor specific auto-discovery tools currently available. In contrast, the physical layer is the lowest layer in the OSI stack thus auto-discovery at the physical layer illuminates equipment operating at the other higher layers in the stack – more importantly in the network.

5 The communication that takes place between neighboring network elements can be accomplished by a point-to-point protocol whereby a network element queries its neighbor across a link, for example an optical link, for configuration information at the far end. The configuration information requested by each network element of its neighbor comprises the subject network element serial number and
10 the unique identifier of the far-end network element's port that connected to the requesting network element.

 In accordance with another aspect of the present invention we developed a Far-End Protocol for communicating connectivity information or network element data between neighboring network elements. In accordance with our Far-End
15 protocol communications between a network element and its neighbor across a link is via 256 byte packets. In the bit stream in each direction the packets are demarcated by using standard Zero Bit Insertion/Deletion (ZBID) flags, such as is done in the HDLC protocol. Each communication transaction consists of a request packet and a response packet.

20 The format of our Request Packet 401 is shown in FIG. 4A. As FIG. 4A shows, the request packet comprise a PacketProtocolIdentifier 408, a SequenceNumber 409, and Padding 410. The Packet Protocol Identifier 408 is a fixed ASCII character string to indicate that the packet is a far-end protocol request packet. It is a fixed ASCII strings that reads FarEndProtocolRequest. The sequence
25 number 409 is an integer that uniquely identifies a request-response sequence. It is

incremented by the requesting network element for each new request-response transaction. After reaching the maximum, this integer wraps around. We allocated four bytes for the sequence number. The padding consists of ASCII blanks to make the packet 256 bytes long. For clarity we include Table 1 below which contains a
5 summary of the function and format of the request packet.

Table 1

Field	Function	Format
PacketProtocol Identifier	This is just a fixed ASCII character string to indicate that this is a Far End Protocol request packet. It is a fixed ASCII string which reads: FarEndProtocolRequest	FarEndProtocol Request (20 bytes)
SequenceNumber	This number uniquely identifies a request-response sequence. It is incremented by the Requesting NE for each new request-response transaction. After reaching the maximum, this integer wraps around.	Integer (4 bytes).
Padding	Padding to make the packet 256 bytes	ASCII blanks (231 bytes)

In FIG. 4B we show the format of our response packet 451 which comprises a PacketProtocolIdentifier 458, a SequenceNumber 459, FarEndElectronicModel
10 Number 471, FarEndElectronicSerial Number 472, FarEndPortIdentifier 473, and Padding 475. Packet Protocol Identifier 458 is a fixed ASCII character string to indicate that this is a Far End Protocol response packet. Sequence Number 459 is the same 4-byte Sequence Number sent by the request packet to which this is a response. Far End Electronic Model Number 471 is an ASCII-encoded electronic
15 model number of the network element product at the far-end. ASCII-encoded Electronic Serial Number of the network element product at the far-end. Far End Electronic Serial Number 472 is an ASCII-encoded electronic serial number of the network element product at the far-end. Far End Port Identifier 473 is a port number, using manufacturer's syntax, which uniquely identifies the port at the far end.
20 Padding 475 is a 38 byte ASCII blank string to make the packet 256 byte in length.

For clarity we included Table 2 below which summarizes the fields, functionality, and format of a response packet.

Table 2

Field	Comment	Format
PacketProtocol Identifier	Fixed ASCII character string to indicate that this is a Far End Protocol response packet.	FarEndProtocol Response
SequenceNumber	The same 4-byte SequenceNumber sent by the Request Packet to which this is a response.	Integer (4 bytes).
FarEndElectronic ModelNumber	ASCII-encoded Electronic Model Number of the NE product at the far-end.	Char (64 bytes). Left-justified, padded with blanks.
FarEndElectronic SerialNumber	ASCII-encoded Electronic Serial Number of the NE product at the far-end.	Char (64 bytes) left-justified, padded with blanks.
FarEndPort Identifier	Port number, using manufacturer's syntax, which uniquely identifies the port at the far end.	Char (64 bytes) left-justified, padded with blanks.
Padding	Padding to make the packet 256 bytes	ASCII blanks (38 bytes)

5 Where a network element does not respond in a timely manner to a request packet a fixed time-out of approximately one minute is allowed by the requesting network element. We chose one minute for our timeout timer because our protocol is for communication between neighboring network elements. Nonetheless, a timeout time of less than or more than minute may be appropriate depending on the
10 circumstances. In addition, in accordance with this aspect of our invention for a response packet to be accepted as valid by the requesting network element, the packet must arrive in one minute and must have a matching sequence number. Otherwise the packet is discarded.

15 With the network elements able to exchange connectivity information among themselves, that connectivity information may then be communicated to the network management system as is shown at block 350 of FIG. 3. There are two methods for updating the network topology information in the network management system. One

method is network management system-initiated and the other is network element initiated. Both types of updates function concurrently. The network element initiated update ensures that the network-topology information in the network management system is always up-to-date. The network element initiated update is event-triggered, e.g., when a fiber link is connected into a port of the network element. The network management system-initiated update is useful for establishing an initial population for the network management system database, and periodic re-synching with the real network topology.

We now turn to FIGS. 5A and 5B to describe network management system-initiated and network element initiated updates of network topology, respectively.

In FIG. 5A, the network management system initiated update begins at block 510 with a network management system requesting a configuration update from each network elements it knows of. As previously discussed the network management system need not be directly connected to each network element that it knows of. As a practical matter, the network management system need only be connected to a gateway network element within each domain and use the gateway network element to communicate to all other network elements within that domain. Further, the protocol for communication between the network management system and the network elements can be any of the standard Operating System/Network Element (OS/NE) protocol such as, for example, SNMP, TL/1, CORBA, or a proprietary protocol.

On receiving a configuration update request the network element uses a point-to-point protocol, such as our far-end protocol, to request connectivity information of all its neighbors, block 515. Ports that are not active, i.e., not connected will result in a null response. Ports that are connected respond with the

far-end model number and serial number and the far end port identifier, block 520.

The network element then sends the network management system a block of information about itself, block 525. The information then includes the network element model number, network element serial number, and for each connected port on the network element the port identifier, far end network element model number, far end network element serial number, and the far end network element port identifier. If a port is a null then a null packet is sent for that port.

We now turn to FIG. 5B to discuss the method for a process initiated update.

At block 570 the method begins with a trigger event. The following events can serve as triggers: the network element is powered up or a link is connected or disconnected. Once the trigger event occurs, the network element transmits a message to the network management system to inform the network management system that it will be updating its configuration, block 572. The network element then uses the Far End Protocol to gather a block of information about itself, block 575.

The block of information includes the same information gathered at block 525 in FIG. 5A. Specifically, the information includes the network element model number, network element serial number, and for each connected port on the network element the port identifier, far end network element model number, far end network element serial number, and the far end network element port identifier. If a port is a null then the null packet is sent for that port. The network element then sends the block of information to the network management system, block 580

By using the methods described in FIG. 5A and FIG. 5B a network management system acquires more than sufficient information to determine the entire physical layer connectivity of the network. A network management system

operating in accordance with our invention is therefore able to automatically keep current with the real network topology as the network evolves.

To further clarify our invention, we turn to FIG. 6 which depicts an exemplary network designed and operating in accordance with the aspects of our invention described above. The network of FIG. 6 is merely illustrative and is used only to further explain the benefits and advantages of our invention. FIG. 6 illustrates a network management system 610 communicating with ATM domain, SONET domain, and IP domain network elements. In particular, ATM switch 615 is connected to SONET network element 620, routers 622 and 624, and network management module 610. SONET network element 620 is connected to SONET network element 628 and network management module 210.610. SONET network element 628 is connected to router 629. Router 629 is also connected to network management system 610. In addition, router 629, network elements 620 and 628, and switch 615 each include auto-discovery functional module 255, processor 252, and electronic serial number module 251.

In addition to communicating with switches, routers and other network elements comprising a network, network management 610 module optionally includes links to downstream fault management, performance management and other administrative systems 650. The information stored in network management system 610 can be used by these systems 650 to perform their respective functions.

In accordance with our invention, the network management function 610 has a topology view of the network that preserves the relationships between the circuits and ports at different layers. Including the relationship between circuit and ports at different layers represents a significant advance over the prior art. This integrated view of the network topology is extremely useful, not only for provisioning and

assignments, but also for fault management and performance management. In accordance with our invention, to add a new network element to the network, a network support person wires up the network element as desired. The network management function 610 instantly gets a current topology view of the network, including the new network element. The new network element at the instant it is connected to the existing network is ready for carrying service and can be monitored for performance. If, subsequently, physical links are changed or re-assigned, the network management module reflects the changes in topology within any domain. In accordance with our invention when a network element vendor product hits the market, the software changes required in network management functionality are minimal, or non-existent.

In particular, network management system 610 by being connecting to ATM switch 615, SONET/WDM network element 620, and router 629 can autonomously construct a more accurate network topology. ATM switch 615 would be able to gain knowledge of all its neighboring network elements ~~220, 222, and 224~~620, 622, and 624 by executing our far end protocol over the OC-3 and T1 links to each of these respective network elements. SONET/WDM 220 network element would be able to relay connectivity information about its neighboring network elements 215 and 228. In addition, router 229 would indicate its connection to network element 228. As previously discussed, the network elements directly connected to the network management system would also serve as gateways to not only its neighbors but to all the subtending network elements that form part of that domain's network. For example, by being connected to SONET/WDM network element 620 the network management system would be able to construct the entire optical network 666 connected to network element 620.

The above description has been presented only to illustrate and describe the invention. It is not intended to be exhaustive or to limit the invention to any precise form disclosed. Many modifications and variations are possible in light of the above teaching. The applications described were chosen and described in order to best explain the principles of the invention and its practical application to enable others skilled in the art to best utilize the invention on various applications and with various modifications as are suited to the particular use contemplated.

11/27/2017 11:27:27 AM C:\Users\Banwell\AppData\Local\Microsoft\Windows\Temporary Internet Files\Content.IE5\B7QJ6Q1G\11272017112727AM.jpg

WE CLAIM:

1. A system for managing a network comprising:

a first network element;

a second network element connected to said first network element;

a network management system connected to said first and second network elements; and

wherein said first and second network elements each include means for encoding a unique identifier associated with each of said network elements, a processor coupled to said encoding means, and means for physical layer auto-discovery.

2. The system in accordance with claim 1 wherein said means for physical layer auto-discovery comprises:

a program storage device readable by a processor and tangibly embodying a program of instructions executable by the processor to perform a method of communicating connectivity information between said first and second network elements, the method comprising the steps:

sending a request packet at the physical layer from the first network element to the second network element; and

receiving a respond packet at the physical layer in response to said sent request packet.

3. The system in accordance with claim 2 wherein said request packet comprises a first packet protocol identifier, a sequence number, and a first padding.

4. The system in accordance with claim 2 wherein said response packet comprises a second packet protocol identifier, said sequence number, a far end electronic serial number, a far end port identifier, and a second padding.

1 4. padding.

1 5. The system of claim 1 wherein said first network element is connected to
2 said second network element by an optical fiber link.

1 6. A method for automatically discovering a network topology comprising the
2 steps of:

3 assigning an electronic serial number and unique port identifier to a network
4 element;

5 representing the network element in a network management system based on
6 said assigned electronic number;

7 communicating connectivity information between the network element and a
8 neighboring network element based on said assigned electronic serial number and
9 unique port identifier; and

10 communicating said connectivity information to the network management
11 system so that the connectivity information is associated with said representation of
12 the network element.

1 7. The method in accordance with claim 6 wherein said step of assigning an
2 electronic serial number comprises the steps of assigning a network element model
3 number and a network element serial number.

1 8. The method in accordance with claim 6 wherein said step of representing
2 the network element in a network management system comprises the step of
3 assigning a CORBA object to the network element and associating the CORBA
4 object with said assigned electronic serial number.

1 9. A network element comprising means for encoding an electronic serial
2 number associated with each the network element, a processor coupled to said
3 encoding means, and means for physical layer auto-discovery coupled to said
4 processor and wherein said processor uses the encoded electronic serial number
5 and the autodiscovery means to discover all other network elements linked to the
6 network element.

1 10.A request packet for use in a physical layer auto-discovery protocol
2 comprising a packet protocol identifier, a sequence number, and padding.

1 11.A response packet for use in a physical layer auto-discovery protocol
2 comprising a packet protocol identifier, a sequence number, a far end electronic
3 serial number, a far end port identifier, and padding.

ABSTRACT

~~Method~~A method and system for providing autonomous real time updates of a network topology. ~~The method is~~topology are based on a physical layer point-to-point protocol residing in each network element. Either responsive to a request from a network management system or responsive to network trigger event a network initiates a request to its neighboring network elements. The neighboring network elements respond to the request by identifying themselves via an electronic serial number and the port by which they are connected to the requesting network element. The requesting network element then forwards the response to the request to a network management system. The network management system then use the responses to construct a network topology.